

TECHNICAL DATA SHEET

Wallshell® Edge Sealant



Properties

Wallshell® edge sealants are made of Acrylic Resin SS-22, Water, 1,3-Propanediol and Ammonium Hydroxide. It applied on panel edges being cut on-site.

Composition / Information on Ingredients

Substance Name	% in Weight
Acrylic Resin SS-22	60.5%
Water	37.3%
1,3-Propanediol	2%
Ammonium Hydroxide	0.2%

Technical Data

Properties	Average Value
Physical State	Liquid
Appearance	Transparent liquid
Color	Transparent
Odor	Odorless
Freezing Point	0 °C
Boiling Point	100°C
Density	1.20 – 1.35 g/cm ³
pH	8
Dispersion Properties	Can be dispersed in water

Delivery

Packaging
Box

Storage

Storage Conditions
Dry condition

Application Requirements

Apply Wallshell® Edge Sealant: Thoroughly caulk all the joins among panels

Special Information

THE INFORMATION OR DATA IN THIS SHEET SERVES TO ENSURE THE PRODUCT'S INTENDED PURPOSE OR ITS SUITABILITY FOR USE AND IS BASED ON OUR FINDINGS AND EXPERIENCE. NEVERTHELESS, USERS ARE RESPONSIBLE FOR ESTABLISHING THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE. APPLICATIONS OTHER THAN THOSE EXPLICITLY MENTIONED IN THIS TECHNICAL DATA SHEET ARE ONLY PERMISSIBLE AFTER PRIOR CONSULTATION WITH WALPANEL, INC. WHERE NO APPROVAL IS GIVEN, SUCH APPLICATIONS ARE AT THE RISK OF THE USER. THIS APPLIES IN PARTICULAR WHEN THE PRODUCT IS USED IN COMBINATION WITH OTHER PRODUCTS. WHEN A NEW TECHNICAL DATA SHEET IS PUBLISHED, ALL PREVIOUS TECHNICAL DATA SHEETS ARE NO LONGER VALID. THE LATEST VERSION IS AVAILABLE ON THE INTERNET AT WWW.WALLSHELL.COM.